

# GALVPATCH

Conforms to EU Directive 91/155/EEC

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

-Product Name	GALVPATCH ®
-Revision Date	Rev 1 - 03.05.2018
-Product Code	GALPA020
-Manufacturer/Supplier	DRIVELINES & SPRAYFLOW cc
-Address	69 First Street – Boksburg North – Gauteng -RSA
-Telephone Number	011.892.3153/4
-Fax Number	011.917.6683
-Emergency Number	011.892.3153

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Revision Date: 03.05.2018

Name	CAS Number	%	EC No.	Classification
Zinc powder dust (stabilized)	7440-66-9	80-81	231-175-3	N:R50/53
Bisphenol A (epichlorhydrin)	25068-38-6	10-12		Xi: R36/38/43 R43 N: 51/53
Benzyl alcohol	100-51-6	1.5-4	202-859-9	Xn: R20/22
Phenol 4.4 1methylethydyene	161278-17-7	1.5-3.5		Xn: R20/21 C: R34 R43/R53
Orixane, mono (c12-14-alkyloxy)	68609-97-2	1-3	271-846-8	Xi: R38/43 N: R51/53
m-xylene-alpha, alpha-diamine	1477-55-0	1-2.5	216-032-5	Not Classified

See section 16 for full text of the R-phases declared above occupational exposure limits, if available, are listed in section 8.

### 3. HAZARDS IDENTIFICATION

Revision Date: 03.05.2018

Product is classified as dangerous according to Directive 1999/45/EC and its amendments

Classification:	:Xi R36/38,R43 N: R50/53
Physical/chemical hazards	: Not Applicable
Human health hazards	: Irritating to the eyes and skin. May cause sensitization by skin contact
Environmental hazards	: Very toxic to aquatic organisms
Additional hazards	: Not available

See section 11 for more detailed information on health effects and symptom

#### 4. FIRST-AID MEASURES

Revision Date: 03.05.2018

- Ingestion:** Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin Contact:** Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Clothing.** Wash with warm water and soap if necessary.
- Eye Contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**See section 11 for more detailed information on health effects and symptoms**

#### 5. FIRE-FIGHTING MEASURES

Revision Date: 03.05.2018

- Extinguishing media.** Use an extinguisher suitable for surrounding fire. Co2 Water mist
- Specific hazards.** Extreme marine pollutant. Contain any water used in fire or spill and do not allow discharged water into drains or back into the environment.
- Product flammability.** Extremely flammable
- Hazardous bi-products.** De-composition may include: carbon dioxide, carbon monoxide, nitrogen oxides, halogens and metal oxides.
- Fire Fighter Equipment:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### 6. ACCIDENTAL RELEASE MEASURES

Revision Date: 03.05.2018

- Personal Precautions:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

## 6. ACCIDENTAL RELEASE MEASURES (Continued)

Revision Date: 03.05.2018

- Environmental precautions:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities
- Methods for cleaning up:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7. HANDLING AND STORAGE

Revision Date: 03.05.2018

### First aid measure:

- Inhalation:** Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in un-labelled containers. Use appropriate containment to avoid environmental contamination.

### Packing materials Recommended:

Use original containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Revision Date: 03.05.2018

**Ingredient name:** m-xylene-alpha,alpha'-diamine

**Occupational exposure limits:** ACGIH TLV (United States, 1/2004). Skin  
CEIL: 0.1 mg/m<sup>3</sup> Form: All forms

### Exposure controls

- Occupational exposure:** Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits
- Respiratory protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary
- Eye protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 03.05.2018

- Colour:** Grey (large sachet)  
Yellow (Small Sachet)
- Odour:** Neutral
- SG @ 25°C** 3.55 Gr / Ml
- PH-value** Neutral
- Physical State** Liquid
- Solubility** Soluble in the following materials: methanol and diethyl ether.  
Very slightly soluble in the following materials: n-octanol.  
Insoluble in the following materials: cold water and hot water

**10. STABILITY AND REACTIVITY**

Revision Date: 03.05.2018

<b>Stability:</b>	The product is stable.
<b>Conditions to avoid;</b>	Prolonged storage above 50°C may interfere with quality
<b>Material to avoid;</b>	Highly reactive or incompatible with the following materials: oxidizing materials. Reactive or incompatible with the following materials: reducing materials, acids and alkalis. Avoid contact with strong oxidizing agents.
<b>Hazardous decomposition;</b>	Decomposition products may include the following materials: Carbon-dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides

**11. TOXICOLOGICAL INFORMATION**

Revision date: 03.05.2018

**Potential acute health effects:** Exposure to decomposition products may cause a health hazard

<b>Inhalation:</b>	Irritating to mouth and throat
<b>Ingestion:</b>	Serious effects may be delayed following exposure.
<b>Skin contact:</b>	Irritating to skin. May cause sensitization by skin contact
<b>Eye contact:</b>	Irritating to eyes.

**Acute toxicity:** Product/ingredient name (bisphenol A-(epichlorhydrin)

<b><u>Result</u></b>	<b><u>Species</u></b>	<b><u>Dose</u></b>	<b><u>Exposure</u></b>
LD50 Oral	Rat	>1000 mg/kg	-
LD50 Oral	Mouse	>500 mg/kg	-

**Potential chronic health effects**

Carcinogenicity-Mutagenicity:	No known significant effects or critical hazards
Reproductive toxicity:	No known significant effects or critical hazards
Over-exposure signs/symptoms:	No known significant effects or critical hazards

Target organs:	Contains material which causes damage to the following organs: blood, kidneys, the nervous system, liver, upper respiratory tract, skin, eye, lens or cornea.
----------------	---

**12. ECOLOGICAL INFORMATION**

Revision date: 03.05.2018

**Ecotoxicity data**

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
zinc powder - zinc dust (stabilized)	Daphnia magna (EC50)	48 hour(s)	2.8 mg/l
	Pimephales promelas (LC50)	96 hour(s)	0.238 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	0.24 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	0.41 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	0.56 mg/l
Benzyl alcohol	Daphnia magna (LC50)	96 hour(s)	0.57 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	10 mg/l
	Pimephales promelas (LC50)	96 hour(s)	460 mg/l

**Other ecological information****Persistence/degradability**

<u>Ingredient name</u>	<u>BOD<sub>5</sub></u>	<u>COD</u>	<u>ThOD</u>
Benzyl alcohol	1.55 gO <sub>2</sub> /g	-	-
<u>Ingredient name</u>	<u>Aquatic half-life</u>	<u>Photolysis</u>	<u>Biodegradability</u>
zinc powder - zinc dust (stabilized)	-	-	Not readily
Benzyl alcohol	Fresh Water 110 days	-	Inherent
<u>Bioaccumulative potential</u>		<u>&lt; 28 day(s).</u>	
<u>Ingredient name</u>	<u>LogP<sub>ow</sub></u>	<u>BCF</u>	<u>Potential</u>
zinc powder - zinc dust (stabilized)	-	100000	high low
Benzyl alcohol	-		

**13. DISPOSAL CONSIDERATIONS**

Revision date: 03.05.2018

**Waste classification:** Hazardous chemical waste

**Methods of disposal** - Dispose of via a licensed waste disposal contractor. The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. TRANSPORT INFORMATION**

Revision date: 03.05.2018

**International transport regulations**

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
ADR / SANS 10228 Class	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction product: bisphenol A-(epichlorhydrin))	9	III		-
IMDG Class	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	9	III		-
IATA Class	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	9	III		-

**15. REGULATORY INFORMATION**

Revision date: 03.05.2018

**SANS 10265 / EU Regulations Hazard symbol or symbols****Irritant, Dangerous for the environment****Risk phrases:**

R36/38- Irritating to eyes and skin.  
R43- May cause sensitization by skin contact  
R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:**

S2- Keep out of the reach of children  
S24 Avoid contact with skin  
S29- Do not empty into drains.  
S37- Wear suitable gloves.  
S46- If swallowed, seek medical advice immediately and show this container or label.  
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

**Contains:**

Reaction product: bisphenol A-(epichlorhydrin)  
Phenol, 4,4-(1methylethylidene)-bis-polymer  
Orixane, mono [(c12-14-alkyloxy)methyl] derivatives 271-846-8

**Product Use:**

Consumer Industrial Applications

## 16. OTHER INFORMATION

Revision date: 03.05.2018

**Full text of R-phrases referred to in sections 2 and 3 - Europe** : R20/21- Harmful by inhalation and in contact with skin.

R20/22- Harmful by inhalation and if swallowed.

R34- Causes burns.

R38- Irritating to skin.

R36/38- Irritating to eyes and skin.

R43- May cause sensitization by skin contact.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53- May cause long-term adverse effects in the aquatic environment.

**Full text of classifications referred to in sections 2 and 3 - Europe**

: C - Corrosive Xn -

Harmful

Xi - Irritant

N - Dangerous for the environment

**Definition of terms**

: CAS Number : Chemical Abstract Number

EC Number : European Community Inventory Number

OEL - RL : Occupational Exposure Limit - Recommended Limits

ACGIH TLV : American Conference on Government Industrial Hygienists - Threshold Limit Value

NIOSH : National Institute of Occupational Health and Safety (USA)

OSHA PEL (TWA) : Occupational Health and Safety Administration (USA) - Permissible Exposure Limit (Total Weighted Average)

LDLO : Lethal Concentration Low. Lowest concentration in air reported to have caused death in humans or animals

LC50 : Lethal Concentration 40. The single dose of a substance that causes death of 50% of an animal population

ADR : Abbreviation for European Agreement on International Carriage of Dangerous Goods By Road.

IMDG : International Maritime Dangerous Goods

IATA : International Air Transport Association

SANS 10265 : South African National Standard 10265 (Carriage of Dangerous Goods by Road)

### History:

Date of original issue: 21.05.2008

Date of previous issue: 21.05.2008

Revision reference: Rev 1.2018

Revision Date: May 2018

***To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.***

***Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.***

Although the information contained herein is presented in good faith and to the best of Drivelines & Sprayflow cc knowledge and experience. It is made without any warranty or guarantee whatsoever.